

Glasurit® Tri-coat Additive



Application: Additive for 3step colours used in 90 Line mixing formulas to produce translucent effects.

Remarks:

- **2004/42/IIIB(d)(420)419:** The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 419 g/litres.

	Paint system	
	Mixing ratio	90 Line Metallics/Solids (acc. to mixing formula) 100% by vol. 90- (mixingformula incl. 90- M5)
	Reducer	50% by vol. 93-E3 or 93-E3 slow Adjusting Base (stir IMMEDIATELY after having added adjusting base)
	Spray viscosity DIN 4 at 20°C	18 –24 s
	Gravity cup Spraying pressure	HVLP-gravity-feed spray gun: 1.3 mm 2.0 bar 0.7 bar at the nozzle Compliant gravity-feed spray gun: 1.3 -1.4 mm 2.0 bar
	Number of spraycoats	2 + ½ to match effect Film thickness: 10 - 15 µm
	Flash-off at 20°C	approx. 5 minutes after each spraycoat
	Intermediate drying Drying at 20°C Blow dry with Dry Jet	Flash off until mat after each spraycoat.

Please refer to the EU Material Safety Data Sheet for product labelling as required by Directive 1999/45/EC and the respective national rules. The products are suitable for professional use only.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at <http://techinfo.glasurit.com> or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. It cannot be ruled out that this product contains particles < 0.1 µm.

BASF Coatings GmbH
Automotive Refinish Coatings Solutions
Europe
Glasuritstrasse 1
48165 Münster
Germany

