






Glasurit® Spot-Blender

G / X

Application: A specific combination of solvents used to melt in clear coat fade-out areas in spot repairs or when fading out the clear in blend-in repairs.

Remarks: The product can be supplied in a standard product container for spraygun application and also in an aerosol can.

- **2004/42/IIIB(e)(840)839:** The EU limit value for this product (product category: IIB.e) in ready to use form is max 840 g/litre of VOC. The VOC content of this product is 839 g/litres.

	Paint system	Glasurit Spot-Repair	
	Spray viscosity DIN 4 at 20°C	ready for use	
	Gravity cup Spraying pressure	HVLP minijet gun: 0.8 - 1.0 mm	Compliant gravity-feed gun 1.3 mm, 2.0 bar
	Number of spraycoats	2 or 3 spraycoats to the clear coat fade-out areas to melt them in.	
	Drying	As recommended for the Glasurit clear used.	

Please refer to the EU Material Safety Data Sheet for product labelling as required by Directive 1999/45/EC and the respective national rules. The products are suitable for professional use only.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at <http://techinfo.glasurit.com> or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. It cannot be ruled out that this product contains particles < 0.1 µm.

BASF Coatings GmbH
Automotive Refinish Coatings Solutions
Europe
Glasuritstrasse 1
48165 Münster
Germany

