Product name:GLASURIT BASE COAT METALLIC 90-Product code:AJ90-913B 2002Printing date:26.01.2013Revision date:18.01.2013

page 1 of 16 version no. 22 GB EN 0000000003 1

# 01 Section 1: Identification of the substance/mixture and of the company/undertaking

Product identifier
 GLASURIT BASE COAT METALLIC 90- 90-M 99-00 SILVER
 AJ90-913B 2002
 53165878
Relevant identified uses of the substance or mixture and uses
 advised against

Recommended use

Car refinishing products

Customer article no

Details of the supplier of the safety data sheet
BASF Coatings GmbH
Postfach 6123
48136 Muenster
Deutschland
E-mail address
Product-Safety-Coatings@basf.com
Emergency phone
+49/2501/143227
Contact for further information
+49/2501/143688

# 02 Section 2: Hazards Identification

# Classification of the substance or mixture

According to Directive 67/548/EEC or 1999/45/EC

- Flammable.
- Harmful by inhalation, in contact with skin and if swallowed.
- Irritating to eyes and skin.

#### Label elements

According to Directive 67/548/EEC respectively 1999/45/EC ( Annex V, Section A and B)

Danger symbol: Xn Harmful



Product contains: 2-butoxyethanol

Product name:GLASURIT BASE COAT METALLIC 90-Product code: AJ90-913B 2002Printing date: 26.01.2013Revision date: 18.01.2013

page 2 of 16 version no. 22 GB EN 0000000003 2

Risk Warnings
R10
Flammable.
R20/21/22
Harmful by inhalation, in contact with skin and if swallowed.
R36/38
Irritating to eyes and skin.

Labelling for Industrial Users
S23
Do not breathe spray dust/solvent vapour.
S36/37
Wear suitable protective clothing and gloves.
S38
In case of insufficient ventilation, wear suitable respiratory
equipment.

#### Other hazards

# 03 Section 3: Composition/Information on Ingredients

#### Substances

not applicable

#### Mixtures

Chemical nature

polyurethane, organic solvent, aqueous solution, pigment

Hazardous ingredients according to Regulation (EC) No. 1272/2008

CAS no. EINECS no. REACH no. INDEX no. % (weight) Hazard Statement

#### mesitylene

108-67-8 203-604-4 601-025-00-5 0,1 - < 0,2 H226 H335 H411 - Flammable liquids Category 3 - Specific target organ toxicity following single exposure irritating to respiratory system Category 3 - Chronic hazards to the aquatic environment Category 2

**1,2,4-trimethylbenzene** 95-63-6 202-436-9

601-043-00-3

Product name:**GLASURIT BASE COAT METALLIC 90-**Product code:AJ90-913B 2002Printing date:26.01.2013Revision date:18.01.2013

page 3 of 16 version no. 22 GB EN 000000003 3

0,3 - < 0,5H226 H332 H315 H319 H335 H411 - Flammable liquids Category 3 - Acute toxicity Inhalation - vapour Category 4 - Skin corrosion/irritation Category 2 - Serious eye damage/eye irritation Category 2A - Specific target organ toxicity following single exposure irritating to respiratory system Category 3 - Chronic hazards to the aquatic environment Category 2 2-butoxyethanol 111-76-2 01-2119475108-36-XXXX 603-014-00-0 203-905-0 30,0 - < 50,0H302 H312 H332 H315 H319 - Acute toxicity oral Category 4 - Acute toxicity dermal Category 4 - Acute toxicity Inhalation - vapour Category 4 - Skin corrosion/irritation Category 2 - Serious eye damage/eye irritation Category 2 sec-butanol 78-92-2 201-158-5 603 - 127 - 00 - 512,5 - < 15,0H226 H319 H335 H336 - Flammable liquids Category 3 - Serious eye damage/eye irritation Category 2 - Specific target organ toxicity following single exposure irritating to respiratory system Category 3 - Specific target organ toxicity following single exposure Vapours may cause drowsiness and dizziness. Category 3 2,4,7,9-tetramethyl-5-decine-4,7-diol 126-86-3 204-809-1 3,0 - < 5,0H318 H402 - Serious eye damage/eye irritation Category 1 - Acute hazards to the aquatic environment Category 3 naphtha (petroleum), hydrotreated heavy 64742-48-9 265-150-3 01-2119457273-39-XXXX 649-327-00-6 2,0 - < 2,5H226 H304 - Flammable liquids Category 3 - Aspiration hazard Category 1 solvent naphtha (petroleum), light aromatic 649-356-00-4 64742-95-6 265-199-0 0,5 - < 1,0H226 H335 H411 H304 H336 - Flammable liquids Category 3 - Specific target organ toxicity following single exposure

Material Safety Data Sheet Safety data sheet according to Regulation (EC) No. 1907/2006			
Product name: <b>GLASU</b> Product code Printing date Revision date	: <b>AJ90-913B</b> : 26.01.2013	2002	page 4 of 16 version no. 22 3 EN 0000000003 4
- Chronic hazar - Aspiration ha - Specific targ	ds to the ag zard Categor et organ tox	y system Category 3 quatic environment Category 1 ricity following single dizziness. Category 3	_
Hazardous ingre according to Di		/45/EC	
CAS no. % (weight)	EINECS no. Symbol		INDEX no.
<b>mesitylene</b> 108-67-8 0,1 - < 0,2		10-37-51/53	601-025-00-5
<b>1,2,4-trimethyl</b> 95-63-6 0,3 - < 0,5	202-436-9	10-20-36/37/38-51/53	601-043-00-3
<b>2-butoxyethanol</b> 111-76-2 30,0 - < 50,0	203-905-0	01-2119475108-36-XXXX 20/21/22-36/38	603-014-00-0
<b>sec-butanol</b> 78-92-2 12,5 - < 15,0		10-36/37-67	603-127-00-5
<b>2,4,7,9-tetrame</b> 126-86-3 3,0 - < 5,0	204-809-1	41-52/53	
<b>naphtha (petrol</b> 64742-48-9 2,0 - < 2,5	265-150-3	01-2119457273-39-XXXX	649-327-00-6
64742-95-6	265-199-0	<b>, light aromatic</b> 10-37-51/53-65-66-67	649-356-00-4
		ymbols, R-phrases and H dangerous ingredients a	

# 04 Section 4: First Aid Measures

# Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Product name:GLASURIT BASE COAT METALLIC 90-Product code: AJ90-913B 2002Printing date: 26.01.2013Revision date: 18.01.2013

page 5 of 16 version no. 22 GB EN 0000000003 5

If inhaled Remove patient to fresh air and seek medical assistance. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position.

On skin contact Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.

On ingestion If swallowed, rinse mouth with plenty of water (only if the person is conscious) and seek medical advice immediately. Keep the injured person at rest. Do not induce vomiting.

# Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

No data available.

# 05 Section 5: Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media Foam (alcohol resistant), carbon dioxide, powders, water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Unsuitable extinguishing media for safety reasons Water jet

# Special hazards arising from the substance or mixture

Due to the organic compound content of the preparation, fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

#### Advice for fire-fighters

Product name:GLASURIT BASE COAT METALLIC 90-Product code: AJ90-913B 2002Printing date: 26.01.2013Revision date: 18.01.2013

page 6 of 16 version no. 22 GB EN 0000000003 6

Special protective equipment Appropriate breathing apparatus may be required.

Additional information Cool closed containers in the vicinity of the source of fire.

# 06 Section 6: Accidental Release Measures

# Personal precautions, protective equipment and emergency procedures

Due to the organic solvents' content of the product, exclude sources of ignition and ventilate area. Avoid breathing vapours.

#### Environmental precautions

Do not allow to enter drains or watercourses. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

#### Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for diposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents.

#### Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

# 07 Section 7: Handling and Storage

#### Precautions for safe handling

#### Instructions for Safe Handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Avoid inhalation of dust from sanding.

Smoking, eating and drinking are forbidden in application area.

Product name:GLASURIT BASE COAT METALLIC 90-Product code: AJ90-913B 2002Printing date: 26.01.2013Revision date: 18.01.2013

page 7 of 16 version no. 22 GB EN 0000000003 7

For personal protection see section 8. Comply with the health and safety at work laws.

Isolate from sources of heat, sparks and open flame. Do not use any sparking tools.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The Manual Handling Operations Regulations 90/269/EEC may apply to the handling of packages of this product. Refer to the guide weight indicated on the package when carrying out assessments. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in Section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

<u>Information on Fire and Explosion Protection</u> Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air.

Keep container dry and tightly closed in a cool well-ventilated place.

# Conditions for safe storage, including any incompatibilities

#### Requirements for Storage Areas and Containers

Electrical equipment must be explosion-proof to the appropriate standard. Floors must be of conducting type and impermeable to the materials being stored.

Keep container tightly closed. Never use pressure to empty; container is not a pressure vessel. Close containers carefully once opened and store upright in order to prevent any leakage. No smoking. Prevent unauthorized access.

#### Information on Combined Storage

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

8

Product name:	GLASURIT BASE COAT METALLIC 90-	
Product code	: AJ90-913B 2002	page 8 of 16
Printing date	: 26.01.2013	version no. 22
Revision date	: 18.01.2013	GB EN 0000000003
		0

#### Additional Information on Storage Conditions

Always keep in containers of same material as the original one. Observe label precautions. Store in a dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition.

Storage temperature : n.d.a.

# Specific end use(s)

Detailed information can be gained from the relevant technical data sheets.

# 08 Section 8: Exposure Controls/Personal Protection

Control parameters

#### Occupational Exposure Limits

CAS no.		limit values ml/m3 (ppm)	mg/m3
<b>sec-butanol</b>	WEL-L		308
78-92-2	WEL-S		462

#### Exposure controls

#### Engineering Measures

Provide adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

#### Personal protective equipment

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the Personal Protective Equipment at Work Regulations 1992 and the COSHH Regulations.

#### **Respiratory Protection**

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet (sanding/

Product name:	GLASURIT BASE COAT METALLIC 90-
Product code	: AJ90-913B 2002
Printing date	: 26.01.2013
Revision date	: 18.01.2013

page 9 of 16 version no. 22 GB EN 0000000003 9

flatting) should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Use A1P2 breathing-protection half mask in case of contact with aerosols.

<u>Hand Protection</u> Wear protective gloves. Any chemical protection glove certified according to EN 374 is suitable: e.g. nitrile gloves

Material thickness: = 0,7 mm

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye Protection Required when there is a risk of eye contact.

Use tight-fitting protective goggles.

<u>Skin Protection</u> Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Environmental exposure controls

see section 7 and 12

# 09 Section 9: Physical and Chemical Properties

Physical state	: liquid
Colour	: metallic

	fety Data Sheet to Regulation (EC) No. 1907/2006
Product name: <b>GLASURIT BASE COAT</b> Product code : <b>AJ90-913B 2</b> Printing date : 26.01.2013 Revision date : 18.01.2013	
Odour	: specific
рH	: n.d.a.
Change in physical state Boiling temperature/range Melting point/range	: n.d.a. : n.d.a.
Flash point	: +036 °C ISO 3679
Ignition temperature	: > 200 °C solvents
Explosion limits, lower upper	: > 35 g/m3 : n.d.a.
Vapour pressure	: n.d.a.
Density	: 1,022 g/cm3 at 20°C
Solubility in water	: miscible
Viscosity	: >060/6 s at 20°C ISO 2431

# 10 Section 10: Stability and Reactivity

### Reactivity

Stable under recommended storage and handling conditions (see section 7).

# Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

# Conditions to avoid

#### Incompatible materials

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

# Hazardous decomposition products

Product name:GLASURIT BASE COAT METALLIC 90-Product code: AJ90-913B 2002Printing date: 26.01.2013Revision date: 18.01.2013

page 11 of 16 version no. 22 GB EN 0000000003 11

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced.

# 11 Section 11: Toxicological Information

# Information on toxicological effects

The preparation has been assessed following the conventional method of the Dangerous Preparation Directive 1999/45/EC. See Sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Acute toxicity Harmful by inhalation, in contact with skin and if swallowed. <u>Irritati</u>on Irritating to eyes and skin. The liquid splashed in the eyes may cause irritation and reversible damage. Corrosivity Based on available Data, the classification criteria are not met. Sensitisation Based on available Data, the classification criteria are not met. <u>Repeated dose toxicity</u> Based on available Data, the classification criteria are not met. **Carcinogenicity** 

Based on available Data, the classification criteria are not met.

Product name:GLASURIT BASE COAT METALLIC 90-Product code: AJ90-913B 2002Printing date: 26.01.2013Revision date: 18.01.2013

page 12 of 16 version no. 22 GB EN 0000000003 12

<u>Mutagenicity</u> Based on available Data, the classification criteria are not met.

<u>Toxicity for reproduction</u> Based on available Data, the classification criteria are not met.

# 12 Section 12: Ecological Information

#### General

There are no test results available for this product.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details.

The product should not be allowed to enter drains or water courses.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

# Persistence and degradability

Biological degradability of hazardous substances mentioned in section 3:

CAS no. test method biological degradability % mesitylene

108-67-8OECD 301 Areadily bio-degradable1,2,4-trimethylbenzene95-63-6OECD 301 Ahardly bio-degradable2,4,7,9-tetramethyl-5-decine-4,7-diol126-86-3OECD 301 B5solvent naphtha(petroleum), light aromatic64742-95-6OECD 301 Areadily bio-degradable

# 13 Section 13: Disposal Considerations

#### Waste treatment methods

Observe national and local legal requirements.

Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under

Product name:	GLASURIT BASE COAT METALLIC 90-	
Product code	: AJ90-913B 2002	page 13 of 16
Printing date	: 26.01.2013	version no. 22
Revision date	: 18.01.2013	GB EN 0000000003

the Control of Pollution Act and the Environmental Protection Act. Using information provided in this data sheet, advice should be obtained from the Environment Agency whether the special waste regulations apply.

13

#### European list of wastes

Commission Decision 2000/532/EC dated 3rd May, 2000

# 08 01 11\*

Waste from the manufacture, formulation, supply and use (MFSU) and removal of paint and varnish; waste paint and varnish cantaining organic solvents or other dangerous substances

Any waste marked with an asterisk (\*) is considered as a hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

#### Contaminated packaging

Recommendation Containers which are not properly emptied must be disposed pursuant to Directive 91/689/EEC

# 14 Section 14: Transport Information

#### Transport by Road or Rail

UN 1263, Paint, 3, III, (D/E), ADR/RID Special provision 640 E Hazard identification number 30

Sea Transport UN 1263, PAINT, 3, III EMS: F-E, S-E

Air Transport UN 1263, PAINT, 3, III

Special precautions for user none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Additonal Information

"NOT CLASS 3 GOODS" in containers of less than 450 litres; ADR

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons

Product name:GLASURIT BASE COAT METALLIC 90-Product code: AJ90-913B 2002Printing date: 26.01.2013Revision date: 18.01.2013

page 14 of 16 version no. 22 GB EN 0000000003 14

transporting the product know what to do in the event of accident or spillage.

# 15 Section 15: Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Information pursuant to VOC Directive 1999/13/EC (for product as
supplied)
Volatile organic solvents: 54 %
VOC : 55 %
Volatile CMR substances : n.a.
Volatile halogenated substances labelled with R40:
n.a.

#### Details relating to the VOC Directive 2004/42/EC

Subcategory as indicated in Annex IIB	: d
Limit value for maximum VOC content	
as specified in Annex IIB	: 420 g/l
VOC content of the ready-for-use product	
according to ISO 11890-2	: 419 g/l

#### National Regulations

The Control of Substances Hazardous to Health Regulations 2002 The Manual Handling Operations Regulations 1992 Storage of Packaged Dangerous Substances, HS(G)71 The Environmental Protection Act Storage of Flammable Liquids in Containers, HS(G)51

#### Chemical Safety Assessment

Chemical Safety Assessment not required

# 16 Section 16: Other Information

Restricted to professional users.

This Safety Data Sheet is prepared in accordance with Regulation (EC) No 1907/2006, Annex II.

The information contained in this safety data sheet does not relieve users from the obligation to carry out their own risk assessment according to Directive 98/24/EC.

Full text of risk warnings for components listed in section 3

R10

Flammable.

Product name:	GLASURIT BASE COAT METALLIC 90-	
Product code	: AJ90-913B 2002	page 15 of 16
Printing date	: 26.01.2013	version no. 22
Revision date	: 18.01.2013	GB EN 0000000003
		15

# R20

Harmful by inhalation. R20/21/22 Harmful by inhalation, in contact with skin and if swallowed. R36/37 Irritating to eyes and respiratory system. R36/37/38 Irritating to eyes, respiratory system and skin. R36/38 Irritating to eyes and skin. R37 Irritating to respiratory system. R41 Risk of serious damage to eyes. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. H226 Flammable liquid and vapour. н302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. н319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H402 Harmful to aquatic life. H411 Toxic to aquatic life with long lasting effects.

#### Material Safety Data Sheet Safety data sheet according to Regulation (EC) No. 1907/2006 Product name: GLASURIT BASE COAT METALLIC 90-: AJ90-913B 2002 Product code page 16 of 16 Printing date : 26.01.2013 version no. 22 : 18.01.2013 Revision date GB EN 000000003 16 Dangerous for the environment Ν Xi Irritant Xn Harmful For multi-pack systems observe material safety data sheets of all components. Explanation of abbreviations:

http://www.internation.com/internation of abbreviations:
n.d.a. no data available
n.a. not applicable

WEL-L Workplace explosure limit - long WEL-S Workplace explosure limit - short

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.