

# SAFETY DATA SHEET



Date of issue/Date of revision : 11 February 2014

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : DP4000 -2K PRIMER GREY-G7  
**Product code** : D8507/E1  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.  
**Use of the substance/mixture** : Coating.

### 1.3 Details of the supplier of the safety data sheet

PPG Industries Italia SpA  
Via Comasina, I - 20161 Milano, Italy  
Tel: +39 02 6404.1

**e-mail address of person responsible for this SDS** : EurMsdsContact@ppg.com

#### National contact

Nexa Autocolor, Customer Service and Sales Group,  
Needham Road, Stowmarket, Suffolk, IP14 2AD, UK  
Tel: +44 (0) 1449 771771

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** :  
Company emergency telephone number : +39 02 6404.1 (0800-1700)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226  
Aquatic Chronic 2, H411

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : R10  
R67  
N; R51/53

**Physical/chemical hazards** : Flammable.

**Human health hazards** : Vapours may cause drowsiness and dizziness.

**Environmental hazards** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the R phrases or H statements declared above.

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision

: 11 February 2014

## SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms



Signal word

: Warning

Hazard statements

: Flammable liquid and vapour.  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Response

: Collect spillage. IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Storage

: Store in a well-ventilated place. Keep cool.

Disposal

: Not applicable.

Hazardous ingredients

: Not applicable.

Supplemental label elements

: Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

### 2.3 Other hazards

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

Substance/mixture

: Mixture

| Product/ingredient name                                    | Identifiers  | %              | Classification                        |  | Type    |
|--|--|----------------|---------------------------------------|--|---------|
|  |  |                | 67/548/EEC                            | Regulation (EC) No. 1272/2008 [CLP]  |         |
| n-butyl acetate  | REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1  | <15            | R10<br>R66, R67                       | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>(Narcotic effects)                            | [1] [2] |
| trizinc bis<br>(orthophosphate)                            | REACH #:<br>01-2119485044-40<br>EC: 231-944-3<br>CAS: 7779-90-0<br>Index: 030-011-00-6 | >=2.5 -<br><25 | N; R50/53                             | Aquatic Acute 1, H400<br>Aquatic Chronic 1,<br>H410                                    | [1]     |
| Solvent naphtha<br>(petroleum), light arom.<br>: Nota(s) P | EC: 265-199-0<br>CAS: 64742-95-6<br>Index: 649-356-00-4                                | >=5 -<br><10   | R10<br>Xn; R65<br>Xi; R37<br>R66, R67 | Flam. Liq. 3, H226<br>STOT SE 3, H335 and<br>H336 (Respiratory<br>tract irritation and | [1]     |

English (GB)

United Kingdom (UK)

2/15

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision

: 11 February 2014

### SECTION 3: Composition/information on ingredients

|                                     |  |               |   |   |         |
|-------------------------------------|--|---------------|---|---|---------|
| 1,2,4-trimethylbenzene              | EC: 202-436-9<br>CAS: 95-63-6<br>Index: 601-043-00-3                                   | >=2.5 -<br><3 | N; R51/53<br><br>R10<br>Xn; R20<br>Xi; R36/37/38<br>N; R51/53   | Narcotic effects)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2,<br>H411<br>Flam. Liq. 3, H226<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>(Respiratory tract<br>irritation)<br>Aquatic Chronic 2,<br>H411<br>Flam. Liq. 3, H226 | [1] [2] |
| 2-methoxy-<br>1-methylethyl acetate | REACH #:<br>01-2119475791-29<br>EC: 203-603-9<br>CAS: 108-65-6<br>Index: 607-195-00-7  | >=1 -<br><5   | R10   | Flam. Liq. 3, H226  | [2]     |
| xylene                              | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9 | >=1 -<br><5   | R10<br>Xn; R20/21<br>Xi; R38<br><br><b>See Section 16 for<br/>the full text of the R-<br/>phrases declared<br/>above.</b> | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br><br><b>See Section 16 for the<br/>full text of the H<br/>statements declared<br/>above.</b>  | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

|                                   |  |
|-----------------------------------|--|
| <b>Eye contact</b>                | : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.                            |
| <b>Inhalation</b>                 | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| <b>Skin contact</b>               | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.   |
| <b>Ingestion</b>                  | : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.   |
| <b>Protection of first-aiders</b> | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.                       |

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision : 11 February 2014

## SECTION 4: First aid measures

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact : ☒ No known significant effects or critical hazards.  
Inhalation : ☒ No known significant effects or critical hazards.  
Skin contact : ☒ Defatting to the skin. May cause skin dryness and irritation.  
Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact : No specific data.  
Inhalation : ☒ No specific data.  
Skin contact : ☒ Adverse symptoms may include the following:  
irritation  
dryness  
cracking  
Ingestion : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.  
Specific treatments : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.  
Unsuitable extinguishing media : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture : ☒ Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.  
Hazardous combustion products : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
sulfur oxides  
phosphorus oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters : ☒ Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7


Date of issue/Date of revision : 11 February 2014


## SECTION 5: Firefighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** :  specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** :  Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision : 11 February 2014

## SECTION 7: Handling and storage

spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

: Storage temperature: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

#### Recommendations

: Not available.

#### Industrial sector specific solutions

: Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name         | Exposure limit values   |
|---------------------------------|---|
| n-butyl acetate                 | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 966 mg/m <sup>3</sup> 15 minutes.<br>STEL: 200 ppm 15 minutes.<br>TWA: 724 mg/m <sup>3</sup> 8 hours.<br>TWA: 150 ppm 8 hours.                       |
| 1,2,4-trimethylbenzene          | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>TWA: 125 mg/m <sup>3</sup> 8 hours.<br>TWA: 25 ppm 8 hours.  |
| 2-methoxy-1-methylethyl acetate | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 548 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 274 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |
| xylene                          | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 441 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 220 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |



Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision

: 11 February 2014

## SECTION 8: Exposure controls/personal protection

### Product/ingredient name

### Exposure limit values

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs

DNELs - Not available.

### PNECs

PNECs - Not available.

## 8.2 Exposure controls

### **Appropriate engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: ☒ Chemical splash goggles.

#### Skin protection

##### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

##### **Gloves**

: nitrile rubber, butyl rubber, PVC, Viton®

##### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

##### **Other skin protection**

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision : 11 February 2014

## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : >37.78°C
- Flash point** : Closed cup: 23°C
- Evaporation rate** : Not available.
- Material supports combustion.** : Yes.
- Flammability (solid, gas)** : Not available.
- Upper/lower flammability or explosive limits** : Lower: 1%  
Upper: 10%
- Vapour pressure** : Highest known value: 1.5 kPa (11.3 mm Hg) (at 20°C) (n-butyl acetate).  
Weighted average: 0.88 kPa (6.6 mm Hg) (at 20°C)
- Vapour density** : Highest known value: 5 (Air = 1) (3-methoxybutyl acetate). Weighted average: 4.11 (Air = 1)
- Relative density** : 1.32
- Solubility(ies)** : Insoluble in the following materials: cold water.
- Partition coefficient: n-octanol/ water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : > 100 s (ISO 6mm)
- Explosive properties** : Not available.
- Oxidising properties** : Not available.

### 9.2 Other information

No additional information.



Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision

: 11 February 2014

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.  
Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                              | Result                 | Species | Dose                    | Exposure |
|--|------------------------|---------|-------------------------|----------|
| Kaolin   | LD50 Oral              | Rat     | >5000 mg/kg             | -        |
|  | LC50 Inhalation Gas.   | Rat     | 6867 ppm                | 4 hours  |
|  | LC50 Inhalation Vapour | Rat     | >21.1 mg/l              | 4 hours  |
|  | LC50 Inhalation Vapour | Rat     | 2000 ppm                | 4 hours  |
|  | LD50 Dermal            | Rabbit  | >17600 mg/kg            | -        |
| Solvent naphtha (petroleum), light arom. : Nota(s) P | LD50 Oral              | Rat     | 10.768 g/kg             | -        |
|  | LD50 Dermal            | Rabbit  | 3.48 g/kg               | -        |
|  |                        |         |                         |          |
| 1,2,4-trimethylbenzene                               | LD50 Oral              | Rat     | 8400 mg/kg              | -        |
|  | LC50 Inhalation Vapour | Rat     | 18000 mg/m <sup>3</sup> | 4 hours  |
|  | LD50 Oral              | Rat     | 5 g/kg                  | -        |
| 2-methoxy-1-methylethyl acetate                      | LD50 Dermal            | Rabbit  | >5 g/kg                 | -        |
|  |                        |         |                         |          |
| xylene   | LD50 Oral              | Rat     | 8532 mg/kg              | -        |
|  | LC50 Inhalation Gas.   | Rat     | 6670 ppm                | 4 hours  |
|  | LC50 Inhalation Vapour | Rat     | 5000 ppm                | 4 hours  |
|  | LD50 Dermal            | Rabbit  | >1.7 g/kg               | -        |
| carbon black respirable                              | LD50 Oral              | Rat     | 4.3 g/kg                | -        |
|  | LD50 Dermal            | Rabbit  | >3 g/kg                 | -        |
|  | LD50 Oral              | Rat     | >15400 mg/kg            | -        |
| titanium dioxide                                     | LD50 Oral              | Rat     | >10 g/kg                | -        |

**Conclusion/Summary** : Not available.

#### Acute toxicity estimates

| Route                | ATE value    |
|----------------------|--------------|
| Dermal               | 46400 mg/kg  |
| Inhalation (gases)   | 281352.7 ppm |
| Inhalation (vapours) | 647.7 mg/l   |

#### Irritation/Corrosion

English (GB)

United Kingdom (UK)

9/15

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision

: 11 February 2014

## SECTION 11: Toxicological information

**Conclusion/Summary** : Not available.

### Sensitiser

**Conclusion/Summary** : Not available.

### Mutagenicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Specific target organ toxicity (single exposure)

| Product/ingredient name   | Category                 | Route of exposure                  | Target organs  |
|---|--------------------------|------------------------------------|--|
| n-butyl acetate<br>Solvent naphtha (petroleum), light arom. : Nota(s) P | Category 3<br>Category 3 | Not applicable.<br>Not applicable. | Narcotic effects<br>Respiratory tract irritation and<br>Narcotic effects |
| 1,2,4-trimethylbenzene  | Category 3               | Not applicable.                    | Respiratory tract irritation   |

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

| Product/ingredient name                              | Result                         |
|--|--------------------------------|
| Solvent naphtha (petroleum), light arom. : Nota(s) P | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : ☒ No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

**Skin contact** : ☒ Defatting to the skin. May cause skin dryness and irritation.

**Eye contact** : ☒ No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : ☒ No specific data.

**Ingestion** : No specific data.

**Skin contact** : ☒ Adverse symptoms may include the following:  
irritation  
dryness  
cracking

**Eye contact** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision

: 11 February 2014

## SECTION 11: Toxicological information

### Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name                   | Result                                   | Species                                | Exposure |
|---|--|--|----------|
| Barium sulfate<br>n-butyl acetate         | Acute EC50 32000 µg/l Fresh water        | Daphnia - Daphnia magna                | 48 hours |
|   | Acute LC50 32000 µg/l Marine water       | Crustaceans - Artemia salina - Nauplii | 48 hours |
| 1,2,4-trimethylbenzene                    | Acute LC50 62000 µg/l                    | Fish - Danio rerio                     | 96 hours |
|   | Acute LC50 17000 µg/l Marine water       | Crustaceans - Cancer magister - Zoea   | 48 hours |
| 2-methoxy-1-methylethyl acetate<br>xylene | Acute LC50 7720 to 8280 µg/l Fresh water | Fish - Pimephales promelas             | 96 hours |
|   | Acute LC50 161 mg/l Fresh water          | Fish                                   | 96 hours |
|   | Acute LC50 8500 µg/l Marine water        | Crustaceans - Palaemonetes pugio       | 48 hours |
|   | Acute LC50 13400 µg/l Fresh water        | Fish - Pimephales promelas             | 96 hours |

Conclusion/Summary : Not available.

### 12.2 Persistence and degradability

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision : 11 February 2014

## SECTION 12: Ecological information

Conclusion/Summary : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| xylene                  | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential

| Product/ingredient name         | LogP <sub>ow</sub> | BCF         | Potential |
|---------------------------------|--------------------|-------------|-----------|
| n-butyl acetate                 | 1.78               | -           | low       |
| 1,2,4-trimethylbenzene          | 3.63               | 120.23      | low       |
| 2-methoxy-1-methylethyl acetate | 0.56               | -           | low       |
| xylene                          | 3.16               | 7.4 to 18.5 | low       |

### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

### 12.6 Other adverse effects : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other dangerous substances |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 04 metallic packaging    |






Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision : 11 February 2014

## SECTION 13: Disposal considerations


**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport information

|                                 | ADR/RID  | ADN  | IMDG   | IATA   |
|---------------------------------|--|--|--|--|
| 14.1 UN number                  |  UN1263 |  UN1263 |  UN1263   |  UN1263 |
| 14.2 UN proper shipping name    | PAINT  | PAINT  | PAINT  | PAINT  |
| 14.3 Transport hazard class(es) | 3  | 3  | 3  | 3  |
| 14.4 Packing group              | III  | III  | III  | III  |
| 14.5 Environmental hazards      | Yes.   | Yes.   | Yes.   | No.  |
| Marine pollutant substances     | Not applicable.  | Not applicable.  |  (trizinc bis (orthophosphate), Solvent naphtha (petroleum), light aromatic) | Not applicable.  |

### Additional information

**ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**Tunnel code** :  (D/E)

**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

Code : D8507/E1  
DP4000 -2K PRIMER GREY-G7

Date of issue/Date of revision : 11 February 2014

## SECTION 15: Regulatory information

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

Other EU regulations

**15.2 Chemical Safety Assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

**Full text of abbreviated H statements** : H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
(dermal)  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
(inhalation)  
H335 May cause respiratory irritation. (Respiratory tract irritation)  
(Respiratory tract irritation)  
H335 May cause respiratory irritation. May cause drowsiness or dizziness. and (Respiratory tract irritation and Narcotic effects)  
H336 (Respiratory tract irritation and Narcotic effects)  
H336 May cause drowsiness or dizziness. (Narcotic effects)  
(Narcotic effects)  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

**Full text of classifications [CLP/GHS]** : Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4  
Acute Tox. 4, H332 ACUTE TOXICITY (inhalation) - Category 4  
Aquatic Acute 1, H400 ACUTE AQUATIC HAZARD - Category 1  
Aquatic Chronic 1, H410 LONG-TERM AQUATIC HAZARD - Category 1  
Aquatic Chronic 2, H411 LONG-TERM AQUATIC HAZARD - Category 2  
Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3

**Code** : D8507/E1  
**DP4000 -2K PRIMER GREY-G7**

**Date of issue/Date of revision** : 11 February 2014

## SECTION 16: Other information

|                         |   |
|-------------------------|---|
| Skin Irrit. 2, H315     | SKIN CORROSION/IRRITATION - Category 2                |
| STOT SE 3, H335         | SPECIFIC TARGET ORGAN TOXICITY (SINGLE                |
| (Respiratory tract      | EXPOSURE) (Respiratory tract irritation) - Category 3 |
| irritation)             |   |
| STOT SE 3, H335 and     | SPECIFIC TARGET ORGAN TOXICITY (SINGLE                |
| H336 (Respiratory tract | EXPOSURE) (Respiratory tract irritation and Narcotic  |
| irritation and Narcotic | effects) - Category 3                                 |
| effects)                |   |
| STOT SE 3, H336         | SPECIFIC TARGET ORGAN TOXICITY (SINGLE                |
| (Narcotic effects)      | EXPOSURE) (Narcotic effects) - Category 3             |

**Full text of abbreviated R phrases** : R10- Flammable.  
R20- Harmful by inhalation.  
R20/21- Harmful by inhalation and in contact with skin.  
R65- Harmful: may cause lung damage if swallowed.  
R37- Irritating to respiratory system.  
R38- Irritating to skin.  
R36/37/38- Irritating to eyes, respiratory system and skin.  
R66- Repeated exposure may cause skin dryness or cracking.  
R67- Vapours may cause drowsiness and dizziness.  
R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Full text of classifications [DSD/DPD]** : Xn - Harmful  
Xi - Irritant  
N - Dangerous for the environment

### History

**Date of issue/ Date of revision** : 11 February 2014

**Date of previous issue** : 30 December 2013

**Prepared by** : EHS

**Version** : 12

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*