

Material Safety Data Sheet
Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 1 of 15

version no. 17

GB EN 00000000004

1

01 Identification of the substance/mixture and of the company/undertaking

Product identifier

HB130 1L FINE ALUMINIUM

AU28-9130 RM01

53215009

Relevant identified uses of the substance or mixture and uses advised against

Car refinishing products

Customer article no

Details of the supplier of the safety data sheet

R-M Automotive Refinish Ltd

Unit 101 10th Avenue

Deeside Ind. Park, Flintshire CH5 2UA

Great Britain

E-mail address

Product-Safety-Coatings@basf.com

Emergency phone

+44 12 44 281 315

02 Hazards Identification

Classification of the substance or mixture

According to Directive 67/548/EEC or 1999/45/EC

- Flammable.
- Harmful by inhalation, in contact with skin and if swallowed.
- Irritating to eyes and skin.

Label elements

According to Directive 67/548/EEC respectively 1999/45/EC (Annex V, Section A and B)

Danger symbol: **Xn**

Danger classification:

Harmful

Product contains:

2-butoxyethanol

Risk Warnings

R10

Flammable.

R20/21/22

Harmful by inhalation, in contact with skin and if swallowed.

Material Safety Data Sheet
Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 2 of 15

version no. 17

GB EN 00000000004

2

R36/38

Irritating to eyes and skin.

Labelling for Industrial Users

S23

Do not breathe spray dust/solvent vapour.

S36/37

Wear suitable protective clothing and gloves.

S38

In case of insufficient ventilation, wear suitable respiratory equipment.

Other hazards

03 Composition/Information on Ingredients

Substances

not applicable

Mixtures

Chemical nature

polyurethane, organic solvent, aqueous solution, pigment

Hazardous ingredients

according to Regulation (EC) No. 1272/2008

CAS no.	EINECS no.	REACH no.	INDEX no.
---------	------------	-----------	-----------

% (weight)

Hazard Statement

n-propylbenzene

103-65-1	203-132-9	
----------	-----------	--

0,1 - < 0,2

601-024-00-X

H226 H335 H411 H304

- Flammable liquids Category 3
- Specific target organ toxicity following single exposure irritating to respiratory system Category 3
- Chronic hazards to the aquatic environment Category 2
- Aspiration hazard Category 1

mesitylene

108-67-8	203-604-4	
----------	-----------	--

0,1 - < 0,2

601-025-00-5

H226 H335 H411

- Flammable liquids Category 3
- Specific target organ toxicity following single exposure

Material Safety Data Sheet
Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 3 of 15

version no. 17

GB EN 00000000004

3

- irritating to respiratory system Category 3
- Chronic hazards to the aquatic environment Category 2

1,2,4-trimethylbenzene

95-63-6 202-436-9

601-043-00-3

0,3 - < 0,5

H226 H332 H315 H319 H335 H411

- Flammable liquids Category 3
- Acute toxicity Inhalation - vapour Category 4
- Skin corrosion/irritation Category 2
- Serious eye damage/eye irritation Category 2A
- Specific target organ toxicity following single exposure
irritating to respiratory system Category 3
- Chronic hazards to the aquatic environment Category 2

2-butoxyethanol

111-76-2 203-905-0

603-014-00-0

30,0 - < 50,0

H302 H312 H332 H315 H319

- Acute toxicity oral Category 4
- Acute toxicity dermal Category 4
- Acute toxicity Inhalation - vapour Category 4
- Skin corrosion/irritation Category 2
- Serious eye damage/eye irritation Category 2

sec-butanol

78-92-2 201-158-5

603-127-00-5

12,5 - < 15,0

H226 H319 H335 H336

- Flammable liquids Category 3
- Serious eye damage/eye irritation Category 2
- Specific target organ toxicity following single exposure
irritating to respiratory system Category 3
- Specific target organ toxicity following single exposure Vapours
may cause drowsiness and dizziness. Category 3

2,4,7,9-tetramethyl-5-decine-4,7-diol

126-86-3 204-809-1

3,0 - < 5,0

H318 H402 H412

- Serious eye damage/eye irritation Category 1
- Acute hazards to the aquatic environment Category 3
- Chronic hazards to the aquatic environment Category 3

naphtha (petroleum), hydrotreated heavy

64742-48-9 265-150-3

649-327-00-6

3,0 - < 5,0

H226 H304

- Flammable liquids Category 3
- Aspiration hazard Category 1

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**
Product code : **AU28-9130 RM01**
Printing date : 12.11.2011
Revision date : 03.11.2011

page 4 of 15
version no. 17
GB EN 00000000004
4

solvent naphtha (petroleum), light aromatic

64742-95-6 265-199-0 649-356-00-4
0,5 - < 1,0

H226 H411 H304 H336

- Flammable liquids Category 3
- Chronic hazards to the aquatic environment Category 2
- Aspiration hazard Category 1
- Specific target organ toxicity following single exposure Vapours may cause drowsiness and dizziness. Category 3

Hazardous ingredients
according to Directive 1999/45/EC

CAS no. % (weight)	EINECS no. Symbol	REACH no. R phrases	INDEX no.
n-propylbenzene			
103-65-1 0,1 - < 0,2	203-132-9 N,Xn	10-37-51/53-65	601-024-00-X
mesitylene			
108-67-8 0,1 - < 0,2	203-604-4 N,Xi	10-37-51/53	601-025-00-5
1,2,4-trimethylbenzene			
95-63-6 0,3 - < 0,5	202-436-9 N,Xn	10-20-36/37/38-51/53	601-043-00-3
2-butoxyethanol			
111-76-2 30,0 - < 50,0	203-905-0 Xn	20/21/22-36/38	603-014-00-0
sec-butanol			
78-92-2 12,5 - < 15,0	201-158-5 Xi	10-36/37-67	603-127-00-5
2,4,7,9-tetramethyl-5-decine-4,7-diol			
126-86-3 3,0 - < 5,0	204-809-1 Xi	41-52/53	
naphtha (petroleum), hydrotreated heavy			
64742-48-9 3,0 - < 5,0	265-150-3 Xn	10-65-66	649-327-00-6
solvent naphtha (petroleum), light aromatic			
64742-95-6 0,5 - < 1,0	265-199-0 N,Xn	10-51/53-65-66-67	649-356-00-4

The wording of the hazard symbols, R-phrases and H-statements is specified in chapter 16 if dangerous ingredients are mentioned.

Material Safety Data Sheet
Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 5 of 15

version no. 17

GB EN 00000000004

5

04 First Aid Measures

Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled

Remove patient to fresh air and seek medical assistance. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position.

On skin contact

Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes

Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.

On ingestion

If swallowed, rinse mouth with plenty of water (only if the person is conscious) and seek medical advice immediately. Keep the injured person at rest. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

No data available.

05 Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media

Foam (alcohol resistant), carbon dioxide, powders, water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Unsuitable extinguishing media for safety reasons

Water jet

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 6 of 15

version no. 17

GB EN 00000000004

6

Special hazards arising from the substance or mixture

Due to the organic compound content of the preparation, fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Special protective equipment

Appropriate breathing apparatus may be required.

Additional information

Cool closed containers in the vicinity of the source of fire.

06 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Due to the organic solvents' content of the product, exclude sources of ignition and ventilate area. Avoid breathing vapours.

Environmental precautions

Do not allow to enter drains or watercourses. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents.

Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

07 Handling and Storage

Precautions for safe handling

Instructions for Safe Handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 7 of 15

version no. 17

GB EN 00000000004

7

occupational exposure limits.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Avoid inhalation of dust from sanding.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

Isolate from sources of heat, sparks and open flame. Do not use any sparking tools.

Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The Manual Handling Operations Regulations 90/269/EEC may apply to the handling of packages of this product. Refer to the guide weight indicated on the package when carrying out assessments. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in Section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

Information on Fire and Explosion Protection

Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air.

Keep container dry and tightly closed in a cool well-ventilated place.

Conditions for safe storage, including any incompatibilities

Requirements for Storage Areas and Containers

Electrical equipment must be explosion-proof to the appropriate standard. Floors must be of conducting type and impermeable to the materials being stored.

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 8 of 15

version no. 17

GB EN 00000000004

8

Keep container tightly closed. Never use pressure to empty; container is not a pressure vessel. Close containers carefully once opened and store upright in order to prevent any leakage. No smoking. Prevent unauthorized access.

Information on Combined Storage

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Additional Information on Storage Conditions

Always keep in containers of same material as the original one. Observe label precautions. Store in a dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition.

Storage temperature : n.d.a.

Specific end use(s)

Detailed information can be gained from the relevant technical data sheets.

08 Exposure Controls/Personal Protection

Control parameters

Occupational Exposure Limits

CAS no.	limit values	
	ml/m3 (ppm)	mg/m3
sec-butanol 78-92-2	WEL-L	-
	WEL-S	-

Exposure controls

Engineering Measures

Provide adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Personal protective equipment

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the Personal Protective Equipment at Work Regulations 1992 and the

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 9 of 15

version no. 17

GB EN 00000000004

9

COSHH Regulations.

Respiratory Protection

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet (sanding/flatting) should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Use AlP2 breathing-protection half mask in case of contact with aerosols.

Hand Protection

Wear protective gloves.

Any chemical protection glove certified according to EN 374 is suitable: e.g. nitrile gloves

Material thickness: = 0,7 mm

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye Protection

Required when there is a risk of eye contact.

Use tight-fitting protective goggles.

Skin Protection

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Environmental exposure controls

Material Safety Data Sheet
Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 10 of 15

version no. 17

GB EN 00000000004

10

see section 7 and 12

09 Physical and Chemical Properties

Physical state	: liquid
Colour	: metallic
Odour	: specific
pH	: n.d.a.
Change in physical state	
Boiling temperature/range	: n.d.a.
Melting point/range	: n.d.a.
Flash point	: +036 °C ISO 3679
Ignition temperature	: > 200 °C solvents
Explosion limits, lower	: > 35 g/m3
upper	: n.d.a.
Vapour pressure	: n.d.a.
Density	: 1,059 g/cm3 at 20°C
Solubility in water	: miscible
Viscosity	: >060/6 s at 20°C ISO 2431

10 Stability and Reactivity

Reactivity

Stable under recommended storage and handling conditions (see section 7).

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 11 of 15

version no. 17

GB EN 00000000004

11

Conditions to avoid

Incompatible materials

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous decomposition products

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced.

11 Toxicological Information

The preparation has been assessed following the conventional method of the Dangerous Preparation Directive 1999/45/EC. See Sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage.

12 Ecological Information

General

There are no test results available for this product.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment.

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 12 of 15

version no. 17

GB EN 00000000004

12

See section 3 for details.

The product should not be allowed to enter drains or water courses.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

Persistence and degradability

Biological degradability of hazardous substances mentioned in section 3:

CAS no.	test method	biological degradability %
n-propylbenzene		
103-65-1	OECD 301 A	readily bio-degradable
mesitylene		
108-67-8	OECD 301 A	readily bio-degradable
1,2,4-trimethylbenzene		
95-63-6	OECD 301 A	hardly bio-degradable
2,4,7,9-tetramethyl-5-decine-4,7-diol		
126-86-3	OECD 301 B	5
solvent naphtha (petroleum), light aromatic		
64742-95-6	OECD 301 A	readily bio-degradable

13 Disposal Considerations

Waste treatment methods

Observe national and local legal requirements.

Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. Using information provided in this data sheet, advice should be obtained from the Environment Agency whether the special waste regulations apply.

European list of wastes

Commission Decision 2000/532/EC dated 3rd May, 2000

08 01 11*

Waste from the manufacture, formulation, supply and use (MFSU) and removal of paint and varnish;
waste paint and varnish containing organic solvents or other dangerous substances

Any waste marked with an asterisk (*) is considered as a hazardous

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 13 of 15

version no. 17

GB EN 00000000004

13

waste pursuant to Directive 91/689/EEC on hazardous waste.

Contaminated packaging

Recommendation

Containers which are not properly emptied must be disposed pursuant to Directive 91/689/EEC

14 Transport Information

Transport by Road or Rail

UN 1263, Paint, 3, III, (D/E), ADR/RID

Special provision 640 E

Hazard identification number 30

Sea Transport

UN 1263, PAINT, 3, III

EMS: F-E, S-E

Air Transport

UN 1263, PAINT, 3, III

Additional Information

"NOT CLASS 3 GOODS" in containers of less than 450 litres; ADR

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

15 Regulatory Information

Information pursuant to VOC Directive 1999/13/EC (for product as supplied)

Volatile organic solvents: 49 %

VOC : 50 %

Volatile CMR substances : n.a.

Volatile halogenated substances labelled with R40:
n.a.

Details relating to the VOC Directive 2004/42/EC

Subcategory as indicated in Annex IIB : d

Limit value for maximum VOC content
as specified in Annex IIB : 420 g/l

VOC content of the ready-for-use product
according to ISO 11890-2 : 419 g/l

National Regulations

The Control of Substances Hazardous to Health Regulations 2002

Material Safety Data Sheet

Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 14 of 15

version no. 17

GB EN 00000000004

14

The Manual Handling Operations Regulations 1992
Storage of Packaged Dangerous Substances, HS(G)71
The Environmental Protection Act
Storage of Flammable Liquids in Containers, HS(G)51

16 Other Information

Restricted to professional users.

This Safety Data Sheet is prepared in accordance with Regulation (EC) No 1907/2006, Annex II.

The information contained in this safety data sheet does not relieve users from the obligation to carry out their own risk assessment according to Directive 98/24/EC.

Full text of risk warnings for components listed in section 3

R10

Flammable.

R20

Harmful by inhalation.

R20/21/22

Harmful by inhalation, in contact with skin and if swallowed.

R36/37

Irritating to eyes and respiratory system.

R36/37/38

Irritating to eyes, respiratory system and skin.

R36/38

Irritating to eyes and skin.

R37

Irritating to respiratory system.

R41

Risk of serious damage to eyes.

R51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65

Harmful: may cause lung damage if swallowed.

R66

Repeated exposure may cause skin dryness or cracking.

R67

Vapours may cause drowsiness and dizziness.

H226

Flammable liquid and vapour.

H302

Material Safety Data Sheet
Safety data sheet according to Regulation (EC) No. 1907/2006

M

Product name: **HB130 1L FINE ALUMINIUM**

Product code : **AU28-9130 RM01**

Printing date : 12.11.2011

Revision date : 03.11.2011

page 15 of 15

version no. 17

GB EN 00000000004

15

Harmful if swallowed.

H304

May be fatal if swallowed and enters airways.

H312

Harmful in contact with skin.

H315

Causes skin irritation.

H318

Causes serious eye damage.

H319

Causes serious eye irritation.

H332

Harmful if inhaled.

H335

May cause respiratory irritation.

H336

May cause drowsiness or dizziness.

H402

Harmful to aquatic life.

H411

Toxic to aquatic life with long lasting effects.

H412

Harmful to aquatic life with long lasting effects.

N Dangerous for the environment

Xn Harmful

Xi Irritant

For multi-pack systems observe material safety data sheets of all components.

Explanation of abbreviations:

n.d.a. no data available

n.a. not applicable

WEL-L Workplace exposure limit - long

WEL-S Workplace exposure limit - short

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.